



Speed, Performance, Value - The Right Balance

- Low cost and simple to use
- Magnetic damping for faster stability
- Rigid construction for durability
- Zero adjust facility to enable zero reading
- Notched and tiered graduated beams with centre reading
- Stainless steel weighing pan
- Ruler for measuring cm
- Weight holders for storing additional weights
- Security bracket
- Tripod legs for density determination included
- Large stainless steel pan
- Lock down mounting slot for Kensington® type lock and cable
- Weighing
- Below balance weighing
- Density of solids



Technical Specifications

| Model | TBB 2610T | TBB 2610S |
|----------------------|---------------------|-----------|
| Maximum capacity | 2610g | 2610g |
| Readability | 0.1g | 0.1g |
| Tare range | +225g | - |
| Repeatability (S.D.) | 0.2g | 0.2g |
| Linearity (\pm) | 0.2g | 0.2g |
| Pan size | 152mm \varnothing | |

General Specifications

| | |
|----------------------------|----------------|
| Units of measurement | Gram (g) |
| Calibration | External |
| Display | Graduated Beam |
| Housing | Aluminium |
| Overall dimensions (wxdxh) | 505x110x160mm |
| Net weight | 2.7kg |

Key Accessories

- Security Lock and Cable
- Hard Carry Case with Lock



Adam Equipment - offices worldwide

www.adamequipment.com