PGW-M Precision Balances





Available in a wide range of 8 easy-to-use models, the PGW series of precision balances offers unbeatable value for the laboratory. Affordably priced, the PGW boasts advanced features usually found in more expensive precision balances, including intuitive software and a simple user interface for easy set-up and operation. The RS-232 interface allows connection to a computer or printer, making it simple to log data, while GLP-compliant printouts enable error-free record-keeping. Standard features on the PGW include a leveling bubble to ensure precise readings, a weigh-below that allows for below-balance weighing when performing density and specific gravity measurements, capacity tracking, stylishly designed all-metal housing to help divert spills and a large stainless steel pan that is removable for easy cleaning or storage. A large, backlit display is simple to read and has integrated dual text prompts. The PGW has a glass draft shield on models with 0.001g readability and they offer internal calibration.

The PGW brings value to labs, offering a complete range of models with advanced features and intuitive software



Features

- Vivid, backlit LCD easily visible in any lighting conditions
- Programmable backlight can be set to "always on," "always off" or "light only when weighing"
- Capacity tracker built into display for easily monitoring possible overloads
- · Scratch-resistant aluminum housing protects internal components
- Colour-coded keys facilitate quick recognition of the most frequently used buttons
- Dual tare keys facilitate operation with either the left or right hand
- Level indicator and adjustable feet ensure proper balance setup for optimum weighing results
- Security slot for optional Kensington-type lock and cable to help prevent theft
- Large, grade 304 stainless steel pan allows easy cleaning
- · Overload protection helps prevent damage to internal components
- RS-232 interface is available to provide speedy connection to computers and printers
- Audible overload alarm warns when capacity is exceeded
- Auto power-off to save energy
- · External calibration allows for verification and adjustment with weights
- Security password control prevents unauthorised access
- Selectable digital filtering for animal/dynamic weighing enables consistent results
 for moving subjects
- Selectable digital filtering helps minimise effects of vibration and disturbances
- · Zero-tracking feature ensures display returns to zero reading
- · AC adapter included

Applications

- Weighing
- Parts counting
- · Percentage weighing
- · Checkweighing
- · Dynamic / animal weighing
- Density determination

About ADAM:

For more than 40 years, professionals worldwide have relied on Adam Equipment for an extensive selection of dependable and affordable weighing equipment. Adam provides the right balance of speed, performance and value.

PGW-M Precision Balances

®
ЛЛ
Ινι

Model	PGW 153M	PGW 253M	PGW 453M	PGW 753M	PGW 1502M	PGW 2502M	PGW 3502M	PGW 4502M
Capacity	150g	250g	450g	750g	1500g	2500g	3500g	4500g
Readability	0.001g	0.001g	0.001g	0.001g	0.01g	0.01g	0.01g	0.01g
Repeatability (S.D.)	0.01g	0.01g	0.01g	0.01g	0.1g	0.1g	0.1g	0.1g
Linearity (+/-)	0.02g	0.02g	0.02g	0.02g	0.2g	0.2g	0.2g	0.2g
Pan Size	140x140mm				192x192mm			
Weighing Units	g, kg, ct							
Stabilisation Time (sec)	2							
Interface	RS-232							
Calibration	Internal automatic calibration							
Display	Backlit LCD with 24mm -high digits							
Power Supply	15VDC 50/60Hz 800mA adapter							
Operating Temperature	10° to 40°C							
Housing	Die-cast aluminum							
Draught Shield	Square 158x158x80mm N/A							
Overall Dim.	251x358x104mm (wxdxh)							
Net Weight	7.6kg							
Approvals	EC type approved							

Accessories

Item number	Description
104008036	Anti-vibration table
106007453	Density kit for 0.001g models only
301007078	. Dust cover
301207077	. In-use cover
1120011156	. ATP thermal printer
3126011263	. ATP thermal printer paper
3126011281	. ATP thermal printer paper (pack of 10)
3074010266	. RS-232 cable (null-modem)
3074010507	. RS-232 to USB adapter (must order corresponding RS-232 cable)
700100046	. Kensington-type lock and cable
600002028	. Adam DU data collection program
3021210953	. Weigh-below hook
700100027	. F1 1g - 100g Calibration Weight Set
700100070	. F1 1g - 2kg Calibration Weight Set
700100008	. F1 500g Calibration Weight
700100007	. F1 100g Calibration Weight
700100009	. F1 1kg Calibration Weight
700100012	. F1 200g Calibration Weight
700100010	. F1 2kg Calibration Weight

Key Accessories







ATP thermal printer

Easy-to-use features combined with quick set-up equals a truly versatile thermal printer. A single push-button feed key and three easy-to-read LED indicators make operation simple.

Anti-vibration table The AVT anti-vibration table offers a solid, stable surface to help decrease vibration during the operation of analytical or precision balances. The AVT can help reduce fluctuations and inconsistency in measurement resulting from environmental affects.

AdamDU data collection **program** Adam DU software connects

a balance to the laboratory network, helping to achieve seamless data collection, transfer and analysis. DU features an easy-to-use interface with a main command window, allowing users to quickly collect information from up to eight Adam balances simultaneously using RS-232 or USB connections.

Supplied by

www.adamequipment.com